

Lobe Config	Stages	Oper Diff	Flow Range	Rev / Gal	Max Torque	Max WOB	Max Diff
-------------	--------	-----------	------------	-----------	------------	---------	----------

**4 3/4"**

5/6	8.3	1,040	100-300	1.02	3,968	20,000	1,750
7/8	3.1	390	100-275	0.31	7,033	20,000	910
7/8	5.0	625	150-300	0.69	5,612	20,000	1,470

**5" - 5 5/8"**

6/7	8.0	1,200	150-350	0.84	5,897	25,000/45,000	2,065
6/7	8.8	1,200	150-400	0.68	8,014	25,000/45,000	2,240
6/7	11.7	1,200	150-350	0.89	7,658	25,000/45,000	2,905
7/8	4.0	800	250-400	0.30	9,371	25,000/45,000	1,190
7/8	7.0	1,200	150-400	0.49	9,837	25,000/45,000	1,824

**6 1/4"**

7/8	4.8	900	150-400	0.36	10,078	30,000	1,365
-----	-----	-----	---------	------	--------	--------	-------

**6 1/2" Hybrid**

6/7	5.0	625	300-600	0.31	9,762	30,000	1,260
-----	-----	-----	---------	------	-------	--------	-------

**6 3/4"**

4/5	7.0	875	300-600	0.50	5,571	40,000	1,260
6/7	5.0	625	300-600	0.31	9,762	40,000	1,260
7/8	3.3	415	300-600	0.15	15,614	40,000	945
7/8	6.4	1,000	300-600	0.28	15,639	40,000	1,820

**6 5/8" - 7"**

5/6	9.4	1,350	300-700	0.40	11,729	55,000	2,030
5/6	8.4	1,250	350-700	0.35	11,771	55,000	1,785
7/8	6.9	1,050	300-700	0.25	19,010	55,000	1,960
8/9	4.3	650	400-700	0.15	22,828	55,000	1,400

**7 3/4" - 8"**

4/5	5.3	665	400-900	0.26	8,371	60,000	945
6/7	4.0	850	300-900	0.18	13,698	60,000	1,015
7/8	2.2	500	600-900	0.09	18,474	60,000	665
7/8	5.9	750	400-900	0.16	22,020	60,000	1,390

**8 3/4"**

7/8	7.0	1,600	400-1,100	0.18	28,408	70,000	2,135
8/9	4.0	900	600-1,100	0.09	32,935	70,000	1,158

**9 5/8"**

6/7	5.0	900	600-1,200	0.13	21,731	70,000	1,260
-----	-----	-----	-----------	------	--------	--------	-------